

INTEGRITY TESTING LABORATORIES,

a division of ErgoLabs, Inc.

CLIENT:

Versa Products
13923 Doty Avenue
Hawthorne, CA 90250
Attn: John Paul Nelson

LABORATORY NO: F0703171-1
DATE: March 17, 2007
CLIENT P.O. NO.: Fax, JP Nelson
STANDARD: ANSI/BIFMA X5.5-98

SAMPLE: ONE COMPUTER DESK, SPLIT LEVEL CLASSROOM TABLE,
ADJUSTABLE LEG STYLE, 35" DEPTH,
SIZES 30" WIDE TO 72" WIDE, TESTED WITH GLIDES

ABSTRACT

This report serves to document the testing of the above sample tables to all applicable test paragraphs of ANSI/BIFMA X5.5-1998, tests for office desk and table products. All applicable tests required for complete certification were performed on the largest size sample listed above. Observations were made on all of the smaller sizes of this same series and considered to conform by similarity, as construction details were identical. The remainder of this report will show how the table submitted for testing met the requirements needed for conformance to the stated test paragraphs of the standard.



SPLIT LEVEL CLASSROOM SERIES TABLE, ADJUSTABLE LEG MODEL ST7235-BB

3911 E. LaPalma, Suite E, Anaheim Hills, CA 92807 Phone: (714) 630-2363 Fax: (714) 630-2256

This report applies only to the sample or samples submitted for testing and is not necessarily indicative of the quality or condition of apparently identical or similar products. As a mutual protection to clients, the public, or these laboratories, this report is submitted and accepted for the exclusive use of the client to whom it is addressed, and upon that condition that it not be used, in whole or in part, in any advertising or publicity matter without prior written authorization from these laboratories.

RESULTS

Test Paragraph	Test Description	Test loads and Cycles	Observations
4	Concentrated Functional Load	200 lb. load applied 1" from table edge for a period of 60 minutes	PASS-No failure during or after the load application
4.3	Distributed Functional Load	1.5 lb./in of perimeter, or 264 lb. load applied 8" from table edge for a period of 60 minutes	PASS-No failure during or after the load application
4.4	Concentrated Proof Load	300 lb. load applied 1" from table edge for a period of 15 minutes	PASS-No failure during or after the load application
4.5	Distributed Proof Load	2.3 lb./in of perimeter, or 404 lb. load applied 8" from table edge for a period of 15 minutes	PASS-No failure during or after the load application
5	Top Load Ease Test	200 lb. shot filled bag lifted and set 1" from the table edge for a total of 20,000 cycles	PASS-No loss of serviceability after the performance of the test
10	Racking Test	Each end of the sample was raised to a 45-degree angle and supported for a 30-minute period.	PASS-No loss of serviceability after the performance of the test
11	Drop Test	Each end of the sample was raised to 10" above a test platform and released allowing it to impact the platform.	PASS-No loss of serviceability after the performance of the test
12.3	Functional Leg Strength Test	Table was laid on its top and loads of 50 lbs. and 100 lbs. were each applied horizontally within 1" of the end of the leg in two directions	PASS-No loss of serviceability after the performance of the test
12.5	Proof Leg Strength Test	Table was laid on its top and loads of 75 lbs. and 150 lbs. were each applied horizontally within 1" of the end of the leg in two directions	PASS-No sudden major change in the structural integrity of the product
13.3	Stability Test	125 lbs. was applied 1" from table edge at the least stable location	PASS-Unit did not tip over

CONCLUSION

During the execution of the testing program, the Split Level Classroom Table with any combination of 30"-72" width, with glides, performed well with no structural failures or loss of serviceability. These samples submitted for testing **conform** to all of the applicable test paragraphs of ANSI/BIFMA X5.5-1998.

Respectfully submitted,


Edwin A. Leach, Project Manager
INTEGRITY TESTING LABORATORIES,
a division of ErgoLabs, Inc.

