

# ***INTEGRITY TESTING LABORATORIES,***

*a division of ErgoLabs, Inc.*

## **CLIENT:**

Versa Products  
13923 Doty Avenue  
Hawthorne, CA 90250  
Attn: Dan Weber

LABORATORY NO: F0802035-3  
DATE: March 1, 2008  
CLIENT P.O. NO.: Email, D. Weber  
STANDARD: ANSI/BIFMA X5.5-98

**SAMPLE:** ONE ART TABLE, MODEL AT48  
30" DEPTH, 48" WIDE, TESTED WITH GLIDES

## **ABSTRACT**

This report serves to document the testing of the above sample to all applicable test paragraphs of ANSI/BIFMA X5.5-1998, tests for office desk and table products. All applicable tests required for complete certification were performed. The remainder of this report will show how the sample submitted for testing met the requirements needed for conformance to the stated test paragraphs of the standard.



**ART TABLE, MODEL AT48**

3911 E. LaPalma, Suite E, Anaheim Hills, CA 92807 Phone: (714) 630-2363 Fax: (714) 630-2256

This report applies only to the sample or samples submitted for testing and is not necessarily indicative of the quality or condition of apparently identical or similar products. As a mutual protection to clients, the public, or these laboratories, this report is submitted and accepted for the exclusive use of the client to whom it is addressed, and upon that condition that it not be used, in whole or in part, in any advertising or publicity matter without prior written authorization from these laboratories.



**RESULTS**

Paragraph	Test Description	Test loads and Cycles	Observations
4	Concentrated Functional Load	200 lb. load applied 1" from table edge for a period of 60 minutes	<b>PASS</b> -No failure during or after the load application
4.3	Distributed Functional Load	1.5 lb./in of perimeter, or 234 lb. load applied 8" from table edge and 66 lbs on keyboard tray for a period of 60 minutes	<b>PASS</b> -No failure during or after the load application
4.4	Concentrated Proof Load	300 lb. load applied 1" from table edge for a period of 15 minutes	<b>PASS</b> -No failure during or after the load application
4.5	Distributed Proof Load	2.3 lb./in of perimeter, or 360 lb. load applied 8" from table edge and 100 lbs on keyboard tray for a period of 15 minutes	<b>PASS</b> -No failure during or after the load application
5	Top Load Ease Test	200 lb. shot filled bag lifted and set 1" from the table edge for a total of 20,000 cycles	<b>PASS</b> -No loss of serviceability after the performance of the test
10	Racking Test	Each end of the sample was raised to a 45-degree angle and supported for a 30-minute period.	<b>PASS</b> -No loss of serviceability after the performance of the test
11	Drop Test	Each end of the sample was raised to 10" above a test platform and released allowing it to impact the platform.	<b>PASS</b> -No loss of serviceability after the performance of the test
12.3	Functional Leg Strength Test	Table was laid on its top and loads of 49 lbs. and 98 lbs. were each applied horizontally within 1" of the end of the leg in two directions. Sample side panel was modified from original design.	<b>PASS</b> -No loss of serviceability after the performance of the test
12.5	Proof Leg Strength Test	Table was laid on its top and loads of 74 lbs. and 147 lbs. were each applied horizontally within 1" of the end of the leg in two directions. Sample side panel was modified from original design.	<b>PASS</b> -No sudden major change in the structural integrity of the product
13.3	Stability Test	125 lbs. was applied 1" from table edge at the least stable location	<b>PASS</b> -Unit did not tip over

**CONCLUSION**

During the execution of the testing program, the Art table AT48, with glides, performed well with no structural failures or loss of serviceability. This sample submitted for testing **conforms** to all of the applicable test paragraphs of ANSI/BIFMA X5.5-1998.



Respectfully submitted,

*[Signature]*  
 Edwin A. Leach, Project Manager  
 INTEGRITY TESTING LABORATORIES,  
 a division of ErgoLabs, Inc.